

Perry  
B  
346

# SURVEY FOR: MICHAEL J. STEARNS

PT. NE 1/4, SEC. 28  
T-3-N R-12-E  
PERRY TWP., WOOD CO., OHIO

N 1/4 Cor  
Sec. 28  
Capped Iron Rod Fd  
(Prev. Sur)

Mary E. Stahl et al  
Vol. 715, Pg. 1011  
NS3-312-2800-00-008-000

Dennis K. Meek et al  
Vol. 704, Pg. 622  
NS3-312-2800-00-007-000

Found capped iron  
rod 5.15' north of point.

Int. Cor  
Sec. 28  
RR Spike Fd  
(Co. Ref.)


The bearings referred to herein are based upon an assumed meridian and are used only for the purpose of angular measurement.  
(40' Record Right of Way as per Wood Co. Engineer's Office)

N-88°-33'-33"-E  
1647.60'

≡ LUMAN ROAD ≡

North Line, NW 1/4, Sec. 28

NE Cor  
Sec. 28  
RR Spike Fd  
(Co. Ref.)



LEGEND  
● = Capped 5/8 Inch Iron Rod Set  
● = P.K. Nail Set

50.000 Acres  
0.756 Acres in Right of Way

1322.42'  
S-00°-03'-57"-E

East Line, NW 1/4, Sec. 28


≡ BAIRD ROAD ≡

I HEREBY CERTIFY THIS SURVEY TO BE CORRECT AND TRUE TO THE BEST OF MY KNOWLEDGE.

*Michael D. Barnhise*  
MICHAEL D. BARNHISEL  
REG. SURVEYOR #S-7678  
MARCH 16, 2011.

Michael J. Stearns Tr  
Vol. 2743, Pg. 575  
NS3-312-2800-00-002-002

Jacob L. Stearns  
Vol. 3025, Pg. 33  
NS3-312-2800-00-003-000



South Line, NW 1/4, Sec. 28  
≡ PELTON ROAD ≡

E 1/4 Cor  
Sec. 28  
Bait Fd  
(Co. Ref.)

Perry  
B  
346